



# 2684 ES/RT 3084 ES/RT

## Construction Grade Diesel & Electric Rough Terrain Speed Level® Sigma Lifts

- Up to 1,700 lbs. (770 kg) Platform Capacity
- Platform Leveling on Slopes, Automatic or Manual Selection, with an Impressive 14° Side to Side and 10° Fore and Aft Slope Leveling Capability
- 4wd Power Package Giving 45% Gradeability
- Proportional Drive and Lift Controls
- Non-Skid Metal Deck Construction
- Large Sheet Loading Entrances (Fore and Aft)
- No-Maintenance Bearings

**Unique Sigma Lift Design to Drive on Planar Slopes While Being Fully Elevated**



## Standard Features

### Work Area

Roll-Out Deck Extension with Incremental Locking Positions (2684 Models)  
 Standard Swing Gate  
 110v Power to Platform  
 Automatic Platform Leveling  
 Large Sheet Material Loading Entrance  
 Lanyard Attachments

### Performance

Up to 45% Gradeability  
 Fully Proportional Drive and Lift Controls  
 Oscillating Axle  
 4WD with Traction Control

### Power

RT - Kubota Tier 4 Final Engine  
 ES - DC Battery with Battery Charge Indicator and Industrial Grade, Solid State Battery Charger

### Serviceability

Lubrication-Free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical Components  
 Logically Grouped Components and Numbered Wiring for Easy Reference

### Safety

Lift Control Orientation to Mitigate Overhead Entrapment	Non-Skid Metal Deck Construction
Dedicated Compartments Protect Electrical and Hydraulic Components	Drive Speed Interlock
Emergency Shut-Off at Platform and Lower Controls	Multi-Axis Tilt Sensor
All Motion Alarm	Multiple Disc Brakes, Manual Brake Release
	Four Wheel Automatic Parking Brake
	Flashing Beacon
	Automotive Horn

### Other Features

Standard On-Board Diagnostics  
 Removable Upper Controls  
 Fold-Down Guardrails  
 Hour Meter  
 Machine Tie Downs  
 Standard Foam Filled RT Tires

## Optional Features

Air Line to Platform  
 Cold Weather Package  
 Platform Work Lights  
 Tires - Non-Marking  
 Pipe Rack  
 Second Year Extended Warranty

### RT Model Options:

AC Generator  
 Dual Fuel  
 Diesel Scrubber

### ES Model Options

AC Inverter  
 420Ah Deep Cycle Batteries



### MEC Aerial Work Platforms

Tel: 559.842.1500 | Fax: 559.842.1520

Toll free: 1.877.MEC LIFT | 1.877.632.5438

1401 S. Madera Avenue, Kerman, CA 93630 | USA

Email: info@MECawp.com | www.MECawp.com

MEC® and Speed Level® are registered trademarks of California Manufacturing & Engineering Co., LLC. 97013 DTD 0121

Speed Level® Models	2684RT Diesel	2684ES Electric	3084RT Diesel	3084ES Electric
<b>Heights</b>	<b>U.S./Metric</b>		<b>U.S./Metric</b>	
Working Height*	32 ft.* / 9.75 m*		36 ft.* / 11 m*	
Platform Height	26 ft. / 7.93 m		30 ft. / 9 m	
Maximun Drive Height	26 ft. / 7.93 m		30 ft. / 9 m	
Stowed Height (Top Guardrail)	105 in. / 267 cm			
Stowed Height (Rails Folded)	70 in. / 178 cm			
Guardrail Height	43.5 in. / 110 cm			
Toeboard Height	6 in. / 15 cm			
Ground Clearance	10 in. / 25 cm			
<b>Dimensions</b>				
Length-Stowed (Overall)	12.5 ft. / 3.8 m		14.5 ft. / 4.4 m	
Width	7 ft. / 2.1 m			
Platform Length (Extended)	15 ft. / 4.6 m		14 ft. / 4.27 m	
Platform Length (Retracted)	12 ft. / 3.7 m		-	
Platform Width	72 in. / 182 cm			
Wheelbase	100 in. / 254 cm			
Total Lift Capacity	1,700 lbs. / 770 kg		1,500 lbs. / 680 kg	
Extension Deck Lift Capacity	500 lbs. / 227 kg		-	
Structure Leveling	14° Side to Side, 10° Fore and Aft			
<b>Speed</b>				
Raise/Lower Speed	25/35 sec.	30/35 sec.	30/40 sec.	35/40 sec.
Drive Speed (Stowed)	4 mph/6.4 km/h	3 mph/4.8 km/h	4 mph/6.4 km/h	3 mph/4.8 km/h
Drive Speed (Elevated)	.4 mph / .6 km/h			
<b>Performance</b>				
Gradeability	45% / 24.2°	40% / 22°	45% / 24.2°	40% / 22°
Turning Radius (Inside)	8 ft. / 2.44 m			
Turning Radius (Outside)	16.7 in. / 5.08 m			
Weight**	8,100 lbs.** / 3,674 kg**		8,580 lbs.** / 3,892 kg**	
Brakes	4 Wheel Multi-Disc			
Power Source	RT = Kubota D1105; ES = Eight 6V 370Ah Ind. Deep-Cycle Batteries			
Controls	Proportional Drive & Lift Controls			
Tires	26 x 12D / 380NHS			
Fuel Capacity (Diesel Only)	15 gal. / 57 L	-	15 gal. / 57 L	-
Hydraulic Fluid Capacity	23 gal. / 87 L			

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

\*\*Weight may vary with certain options or configurations. When platform is elevated, all models must be on a firm, planar surface.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: